

PRODUCT DATA SHEET

Name **DeoAdd 1230**
(former DeoAdd 1030)

Description EP – Additive

Composition sulphurized olefins

Appearance amber liquid

Analytical Values*

Sulphur	[%]	DIN 51724-3	28.5 – 30.5
Active Sulphur	[%]	ASTM D 1662	14
Kinematic viscosity at 40 °C	[mm ² /s]	DIN EN ISO 3104	10 – 30
Copper corrosivity (10 % in paraffin oil, 3h at 100 °C)		DIN EN ISO 2160	4

Treat Rate [%] 0.5 – 20.0 %

Supply Form 175 Kg bung hole steel drum
875 Kg ISO Bulk-Container

Storage Stability

In originally sealed package, cool and dry area min. 12 months

Classification and Labelling

For detailed information please refer to our Safety Data Sheet

Application

DeoAdd 1230 is a light coloured, high active sulphur carrier with an active sulphur content of approx. 15 %. Due to its high active sulphur content DeoAdd 1230 can be used as EP-booster for metal working fluids, as well as an EP-additive in industrial lubricants, like e.g. industrial gear oils.

Performance can be increased by combination with antiwear additives, e.g. from our range of Deophos products.

The listed values can not be used to design a product specification.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from August 2020