

Product Data Sheet

Product Name	DeoAdd 1415 (former: VP 390)
Description	EP - Additive
Composition	sulphurized lard oil
Appearance	brown liquid

Analytical Value*

Sulphur	[%]	DIN ISO 51724-3	14.0 – 16.0
Density at 15 °C	[Kg/m ³]	DIN EN ISO 12185	980 - 1020
Kin. Viscosity at 40 °C	[mm ² /s]	DIN EN ISO 3104	400 – 800

Dosage	[%]	up to 40, depending on application
---------------	-----	------------------------------------

Supply Form	200 kg bung hole steel drum
--------------------	-----------------------------

Storage Stability	min. 12 months
in originally sealed package, cool and dry area	

Classification and Labeling

For detailed information please refer to our Safety Data Sheet

Application

DeoAdd 1415 is suitable for formulations of metal working fluids and is especially used if an EP effect and good lubricity is needed. DeoAdd 1415 does not contain metal deactivator and is free of mineral oil.

**The listed values can not be used to design a product specification.*

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from August 2020