

Product Data Sheet

Product Name	DeoAdd 1800 (former: DeoAdd V 300)
Description	EP- / AW- / AO - Additive
Composition	organic sulphur compound
Appearance	light brown, clear liquid

Analytical Value*

Sulphur	[%]	DIN 51724-3	29.0 – 32.0
Density at 25 °C	[Kg/m ³]	DIN EN ISO 12185	1040 - 1080
Kin. Viscosity at 40 °C	[mm ² /s]	DIN EN ISO 3104	340 – 400
Kin. Viscosity at 100 °C	[mm ² /s]	DIN EN ISO 3104	10 – 20

Dosage	[%]	0.5 – 5.0
---------------	-----	-----------

Supply Form	200 kg bung hole steel drum
--------------------	-----------------------------

Storage Stability	min. 12 months
in originally sealed package, cool and dry area	

Classification and Labeling

For detailed information please refer to our Safety Data Sheet

Application

DeoAdd 1800 is a multifunctional ashless additive which can be used as an extreme pressure, antiwear and antioxidant additive.

DeoAdd 1800 is ideally suited for formulating ashless lubricants and greases. DeoAdd 1800 is soluble in comment base oils, but it is recommended to test the solubility, since base oils may differ from supplier to supplier.

The listed values can not be used to design a product specification.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.