

Product Data Sheet

Product Name	DeoAdd MRX 16
Description	EP - Additive
Composition	sulphurized fatty acid ester
Appearance	light brown, clear liquid

Analytical Value*

Sulphur	[%]	DIN 51724-3	15.5 – 16.5
Density at 15 °C	[Kg/m ³]	DIN EN ISO 12185	995 - 1035
Kin. Viscosity at 40 °C	[mm ² /s]	DIN EN ISO 3104	250 – 280

Dosage	[%]	5 - 10
---------------	-----	--------

Supply Form	200 kg bung hole steel drum 1000 kg IBC container
--------------------	--

Storage Stability	min. 12 months
in originally sealed package, cool and dry area	

Classification and Labeling

For detailed information please refer to our Safety Data Sheet

Application

DeoAdd MRX 16 is a light coloured, low odour EP – Additive for metal working fluids, e.g. drilling and cutting oils.

To increase the performance of DeoAdd MRX 16 a combination with fatty oils and zinc dialkyldithiophosphates is recommended. Formulations for metal forming may contain up to 40 % of DeoAdd MRX 16.

The listed values can not be used to design a product specification.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from August 2020