

**Product Data Sheet**

<b>Product Name</b>	<b>DeoAdd MRZ 16</b>
<b>Description</b>	EP - Additive
<b>Composition</b>	sulphurized fatty acid ester
<b>Appearance</b>	brown liquid

**Analytical Value\***

Sulphur	[%]	DIN 51724-3	15.5 – 16.5
Density at 15 °C	[Kg/m <sup>3</sup> ]	DIN EN ISO 12185	955 - 1035
Kin. Viscosity at 40 °C	[mm <sup>2</sup> /s]	DIN EN ISO 3104	240 – 280
Copper corrosivity (10 % in paraffin oil, 3h at 100 °C)		DIN EN ISO 2160	max. 3b

<b>Dosage</b>	[%]	5 - 10
---------------	-----	--------

<b>Supply Form</b>	200 kg bung hole steel drum 1000 kg IBC container
--------------------	--

<b>Storage Stability</b> in originally sealed package, cool and dry area	min. 12 months
--	----------------

**Classification and Labeling**

For detailed information please refer to our Safety Data Sheet

**Application**

DeoAdd MRZ 16 is a low odour EP – Additive for metal working fluids for e.g. drilling and cutting oils and can be used for ferrous and non - ferrous metals.

DeoAdd MRZ 16 is specially recommended for formulations which containing zinc-compounds like zinc dialkyldithiophosphate to increase performance. A combination with fatty oils can also improve lubricity.

*The listed values can not be used to design a product specification.*

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.