

Product Data Sheet

Product Name	Deophos 218
Description	AW- / EP - Additive
Composition	sulphur-phosphorus-compound free of mineral oil
Appearance	light amber liquid

Analytical Value*

Sulphur	[%]	DIN 51724-3	9.5 – 11.0
Phosphorus	[%]		4.5
Density at 15 °C	[Kg/m ³]	DIN EN ISO 12185	1010 - 1050
Kin. Viscosity at 40 °C	[mm ² /s]	DIN EN ISO 3104	15 – 20

Dosage	[%]	0.5 – 3.0
---------------	-----	-----------

Supply Form	200 kg bung hole steel drum 1000 kg ISO-Bulk-Container
--------------------	---

Storage Stability	min. 12 months
in originally sealed package, cool and dry area	

Classification and Labeling

For detailed information please refer to our Safety Data Sheet

Application

Deophos 218 is a metal free AW- and EP – Additive for ashless lubricants. In combination with light coloured, low odour sulphur carriers like DeoAdd M 16 and other additives it is possible to formulate lubricants for several applications, such as water-miscible, non-water-miscible metalworking fluids, multifunctional fluids, hydraulic oils and turbine- and industrial gear oils.

The listed values can not be used to design a product specification.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from August 2020