DeoPhos 218 AW/EP-Additive



Description

DeoPhos 218 is a ashless, EP & AW additiv. Superp in combination with light coloured sulfur carriers of our DeoLube products paradigm DeoAdd M 16 and other additives it is possible to formulate lubricants.

DeoPhos 218 gives high performance pressurebility with excellent AW- results.

DeoPhos 218 ist is free of Chlorine, mineral oil and heavy metals (Zinc).

Application

DeoPhos 218 is a high performance additv, it is possible to formulate lubricants for several applications, such as water-miscible, non-water-miscible metalworking fluids, multifunctional fluids, hydraulic oils and turbine- and industrial gear oils.

Recommendations for use

The concentration of DeoPhos 218 should be between 0,5% and 5 % . Avoid permanent storage temperatures over 50°C.

Typical Physical Properties

v
,5 ASTM D 6481
2,5 ASTM D 6481
040 ASTM D 7042
2 ASTM D 7042
ASTM D 92
b ASTM D 130

Benefits

- Sustainable, based on renewable raw materials
- Best performance for a variety of formulations due to selected raw materials
- Reduced cost : higher production rates due to strong lubricity
- Suitable for aluminium and yellow metals
- Pefect combination with DeoAdd M types
- Improvement of AW- performance
- EP- Performance Additive
- Superb for Metalworking fluids
- Listed on LuSC

Associated products

For optimal results, we recommend the DeoLube portfolio from EP / AW additives to corrosion protection packages. For more information, please contact our Customer Service Center.

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and dispolsal of the product are beyond our reasonable control – we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Health and Safety

Safety data sheets are available in accordance with Regulations (EG) Nr. 1907/2006 Annex II and (EC) No. 1272/2008 .

Version: 12/2022



DOG DEUTSCHE OELFABRIK Gesellschaft für chemische Erzeugnisse mbH & Co. KG

Ellerholzdamm 50 20457 Hamburg/Germany Tel. + 49 40 3118050 info@dog-chemie.de · www.dog-chemie.de The data in this document has been compiled to the best of our knowledge. However, the product may not be suitable for all applications and working environments. Liability or warranty is therefore expressly excluded.