DeoPhos Zn 8 AW/AO/EP-Additive

Description

DeoPhos Zn 8 is a ZnDTP, due to their polarity these corrosion protection additives adhere to the metal surface.

DeoPhos Zn 8 gives high performance pressurebility with excellent AW- results.

DeoPhos Zn 8 is is free of Chlorine

Application

DeoPhos Zn 8 is a high performance additv, it is possible to formulate lubricants for several applications, such as water-miscible, non-water-miscible metalworking fluids, multifunctional fluids, hydraulic oils and turbine- and industrial gear oils.

Recommendations for use

The concentration of DeoPhos Zn 8 should be between 0,5% and 5 % . Avoid permanent storage temperatures over 50°C.

Typical Physical Properties

Colour	light yellow	Zincdi-2- ethylhexyldithiophosphat
Zinc [%]	8,0 - 10,5	ASTM D 6481
Sulfur [%]	15 - 17	ASTM D 6481
Phosphorus[%]	7,0 – 9,0	ASTM D 6481
Density @ 20°C [kg/m³]	1080 - 1180	ASTM D 7042
Kinematic Viscosity @ 40°C [mm²/s]	150 - 300	ASTM D 7042
Flash point COC [°C]	180	ASTM D 92
Copper Corrosion* [*10 % in paraff. oil]	1a - 1b	ASTM D 130

Benefits

- Sustainable, based on renewable raw materials
- Best performance for a variety of formulations due to selected raw materials
- Reduced cost : higher production rates due to strong lubricity
- o Suitable for aluminium and yellow metals
- Pefect combination with DeoAdd MDZ 18: DeoAdd MOZ 16 & MRZ 16
- Improvement of AW- performance
- o EP- Performance Additive
- Superb for Metalworking fluids

Associated products

For optimal results, we recommend the DeoLube portfolio from EP / AW additives to corrosion protection packages. For more information, please contact our Customer Service Center.

Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and dispolsal of the product are beyond our reasonable control – we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Health and Safety

Safety data sheets are available in accordance with Regulations (EG) Nr. 1907/2006 Annex II and (EC) No. 1272/2008 .

Version: 12/2022



DOG DEUTSCHE OELFABRIK Gesellschaft für chemische Erzeugnisse mbH & Co. KG

Ellerholzdamm 50 20457 Hamburg/Germany Tel. +49 40 3118050 info@dog-chemie.de · www.dog-chemie.de The data in this document has been compiled to the best of our knowledge. However, the product may not be suitable for all applications and working environments. Liability or warranty is therefore expressly excluded.

