

Product Data Sheet

Product Name	Deosicc Zn 12 N
Description	Corrosion Inhibitor
Composition	zinc naphthenate in mineral oil
Appearance	light brown, viscous liquid

Analytical Value*

Zinc	[%]	DIN ISO 4619	11.9 – 12.1
Density at 20 °C	[Kg/m ³]	DIN EN ISO 12185	1000 - 1050
Kin. Viscosity at 40 °C	[mm ² /s]	DIN EN ISO 3104	10 – 50
Corrosion prevention (in artificial seawater)		DIN 51585	0

Dosage	[%]	0.5 – 3.0
---------------	-----	-----------

Supply Form	200 kg bung hole steel drum
--------------------	-----------------------------

Storage Stability in originally sealed package, cool and dry area	min. 12 months
--	----------------

Classification and Labeling

For detailed information please refer to our Safety Data Sheet

Application

Corrosion inhibitor for greases as well for hydraulic oils and gas engine oils.

The listed values can not be used to design a product specification.

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from August 2020