

## Product Data Sheet

<b>Product Name</b>	<b>Deosicc Zn 22</b>
<b>Description</b>	Corrosion and Wear Inhibitor
<b>Composition</b>	zinc-2-ethylhexanoate
<b>Appearance</b>	colourless to light yellow, honeylike liquid

### Analytical Value\*

Zinc	[%]	DIN ISO 4619	22.0 – 24.0
Density at 20 °C	[Kg/m <sup>3</sup> ]	DIN EN ISO 12185	1150 - 1250
Kin. Viscosity at 100 °C	[mm <sup>2</sup> /s]	DIN EN ISO 3104	10 – 40

<b>Dosage</b>	[%]	0.5 – 5.0
---------------	-----	-----------

<b>Supply Form</b>	200 kg bung hole steel drum
--------------------	-----------------------------

<b>Storage Stability</b>	min. 12 months
in originally sealed package, cool and dry area	

### Classification and Labeling

For detailed information please refer to our Safety Data Sheet

### Application

Corrosion and wear inhibitor for greases.

*The listed values can not be used to design a product specification.*

Any technical consultation provided by us merely constitutes a guideline without any committal - even with regard to any third party's rights - and will not dispense from the client's examination of the products supplied by us. Processing operations, application and use of our products will be the client's exclusive responsibility. We guarantee the faultless quality of our goods, as defined in our General Terms of Sale and Delivery.

Valid from August 2020