

Deovulc EG 3

Accelerator Blends

Description

Deovulc EG 3 is a blend of accelerators

Composition

Synergistic combination of highly active accelerators, containing ETU

Application

Deovulc EG 3 ist suitable for general application, if requirements to cure rate and / or compression set are to high. It is also for non blooming and non staining EPDM articles. No blooming phenomena have been observed so far. In view of the multitude of possible compounds formulations, freedom from blomm cannot be guaranteed

Dosage

Black loaded compounds: 3 – 5 phr
 Light coloured compounds: 5 – 6 phr
 Sulphur: 1 – 2 phr
 Additional accelerator: not required

Typical physical properties

		Unit
Colour	Beige, non-dusting powder	/
Total Sulphur	30.5 – 33.5	%
Density at 20°C	1.34 – 1.46	g/cm ³

Benefits

Versatile areas of application
 Fast vulcanization
 Bloom free

Associated products

Deovulc EG 3 MF
 Deovulc BG 187 V
 Deovulc BG 383

Storage

In originally sealed package in cool and dry places at max. 25°C
 Storage stability: min. 12 months

Supply Form

20 kg in cardboxes with PE-inliner

German Food Legislation (BfR recommendation XXI)

Not approved

US Code of Federal Regulations, FDA – CFR Title 21, 177.2600

Not listed

Version: 01/2022